

Profipower Wheel Cleaner

Date of compilation: 25/03/2021


Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Profipower Wheel Cleaner
Other means of identification:
UFI: 6RJM-T0J5-R002-JAA8
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
 Relevant uses: Wheel cleaning
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
 AUTOLAND PROSTA SPÓŁKA AKCYJNA
 Ogrodowa 37
 00-873 Warszawa - Poland
 Phone: 0048-32-47 22 531
 autoland_hse@autoland.pl
 http://autoland.pl
- 1.4 Emergency telephone number:**

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
 Eye Irrit. 2: Eye irritation, Category 2, H319
 Skin Sens. 1: Sensitisation, skin, Category 1, H317
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning

Hazard statements:
 Eye Irrit. 2: H319 - Causes serious eye irritation.
 Skin Sens. 1: H317 - May cause an allergic skin reaction.
Precautionary statements:
 P101: If medical advice is needed, have product container or label at hand.
 P102: Keep out of reach of children.
 P264: Wash thoroughly after handling.
 P280: Wear eye protection.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501: Dispose of contents/container according to the separated collection system used in your municipality.
Substances that contribute to the classification
 Sodium mercaptoacetate
UFI: 6RJM-T0J5-R002-JAA8
Labelling for contents:
- | Component | Concentration interval |
|------------------------|------------------------|
| Amphoteric surfactants | % (w/w) < 5 |
| Non-ionic surfactants | % (w/w) < 5 |
| perfumes | |
- Allergenic fragrances: d-limonene (LIMONENE).
- 2.3 Other hazards:**

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aqueous solution of tensoactives

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 367-51-1 EC: 206-696-4 Index: Non-applicable REACH: 01-2119968564-24-XXXX	Sodium mercaptoacetate⁽¹⁾ Self-classified Regulation 1272/2008 Acute Tox. 3: H311; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	5 - <7 %
CAS: 160901-19-9 EC: Non-applicable Index: Non-applicable REACH: 01-2119490233-42-XXXX	Alcohols, C12-13- branched and linear, ethoxylated (>= 2.5 mol EO)⁽¹⁾ Self-classified Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319 - Warning	2,5 - <5 %
CAS: 61789-40-0 EC: 263-058-8 Index: Non-applicable REACH: 01-2120770501-61-XXXX	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts⁽¹⁾ Regulation 1272/2008 Aquatic Chronic 3: H412; Eye Dam. 1: H318 - Danger	1 - <2,5 %
CAS: 532-32-1 EC: 208-534-8 Index: Non-applicable REACH: 01-2119460683-35-XXXX	Sodium benzoate⁽¹⁾ Self-classified Regulation 1272/2008 Eye Irrit. 2: H319 - Warning	1 - <2,5 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts CAS: 61789-40-0 EC: 263-058-8	% (w/w) >=10: Eye Dam. 1 - H318 4<= % (w/w) <10: Eye Irrit. 2 - H319

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 4: FIRST AID MEASURES (continued)**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

- CONTINUED ON NEXT PAGE -

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 0 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Sodium mercaptoacetate CAS: 367-51-1 EC: 206-696-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,06 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,41 mg/m ³	Non-applicable
Alcohols, C12-13- branched and linear, ethoxylated (>= 2.5 mol EO) CAS: 160901-19-9 EC: Non-applicable	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2080 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	294 mg/m ³	Non-applicable
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts CAS: 61789-40-0 EC: 263-058-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,33 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	8,22 mg/m ³	Non-applicable
Sodium benzoate CAS: 532-32-1 EC: 208-534-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	62,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3 mg/m ³	0,1 mg/m ³

DNEL (General population):

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Sodium mercaptoacetate CAS: 367-51-1 EC: 206-696-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,9 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Alcohols, C12-13- branched and linear, ethoxylated (>= 2.5 mol EO) CAS: 160901-19-9 EC: Non-applicable	Oral	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1250 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	87 mg/m ³	Non-applicable
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts CAS: 61789-40-0 EC: 263-058-8	Oral	Non-applicable	Non-applicable	0,833 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,833 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,45 mg/m ³	Non-applicable
Sodium benzoate CAS: 532-32-1 EC: 208-534-8	Oral	Non-applicable	Non-applicable	16,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	31,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,5 mg/m ³	0,06 mg/m ³

PNEC:



Identification	STP	Soil	Intermittent	Oral	Fresh water	Marine water	Sediment (Fresh water)	Sediment (Marine water)
Sodium mercaptoacetate CAS: 367-51-1 EC: 206-696-4	STP	3,2 mg/L	Fresh water	0,038 mg/L	Soil	Non-applicable	Marine water	0,0038 mg/L
	Intermittent	0,38 mg/L	Sediment (Fresh water)	Non-applicable	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
	STP	10000 mg/L	Fresh water	0,08 mg/L	Soil	1 mg/kg	Marine water	0,008 mg/L
	Intermittent	0,003 mg/L	Sediment (Fresh water)	63,83 mg/kg	Oral	Non-applicable	Sediment (Marine water)	6,38 mg/kg
Alcohols, C12-13- branched and linear, ethoxylated (>= 2.5 mol EO) CAS: 160901-19-9 EC: Non-applicable	STP	300 mg/L	Fresh water	0,0032 mg/L	Soil	0,0419 mg/kg	Marine water	0,00032 mg/L
	Intermittent	0,02 mg/L	Sediment (Fresh water)	0,219 mg/kg	Oral	Non-applicable	Sediment (Marine water)	0,0219 mg/kg
	STP	10 mg/L	Fresh water	0,13 mg/L	Soil	0,06 mg/kg	Marine water	0,013 mg/L
	Intermittent	0,305 mg/L	Sediment (Fresh water)	1,76 mg/kg	Oral	0,3 g/kg	Sediment (Marine water)	0,176 mg/kg
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts CAS: 61789-40-0 EC: 263-058-8	STP	10 mg/L	Fresh water	0,13 mg/L	Soil	0,06 mg/kg	Marine water	0,013 mg/L
	Intermittent	0,305 mg/L	Sediment (Fresh water)	1,76 mg/kg	Oral	0,3 g/kg	Sediment (Marine water)	0,176 mg/kg
	STP	300 mg/L	Fresh water	0,0032 mg/L	Soil	0,0419 mg/kg	Marine water	0,00032 mg/L
	Intermittent	0,02 mg/L	Sediment (Fresh water)	0,219 mg/kg	Oral	Non-applicable	Sediment (Marine water)	0,0219 mg/kg
Sodium benzoate CAS: 532-32-1 EC: 208-534-8	STP	10 mg/L	Fresh water	0,13 mg/L	Soil	0,06 mg/kg	Marine water	0,013 mg/L
	Intermittent	0,305 mg/L	Sediment (Fresh water)	1,76 mg/kg	Oral	0,3 g/kg	Sediment (Marine water)	0,176 mg/kg
	STP	300 mg/L	Fresh water	0,0032 mg/L	Soil	0,0419 mg/kg	Marine water	0,00032 mg/L
	Intermittent	0,02 mg/L	Sediment (Fresh water)	0,219 mg/kg	Oral	Non-applicable	Sediment (Marine water)	0,0219 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands



Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022



Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0,02 % weight
V.O.C. density at 20 °C:	0,26 kg/m ³ (0,26 g/L)
Average carbon number:	9,91
Average molecular weight:	143,54 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Colourless

*Not relevant due to the nature of the product, not providing information property of its hazards.

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour:	Characteristic
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	100 - 410 °C
Vapour pressure at 20 °C:	2350 Pa
Vapour pressure at 50 °C:	12380,54 Pa (12,38 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	1050 kg/m ³
Relative density at 20 °C:	1,05
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	7 - 9
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	225 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: d-limonene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

** Changes with regards to the previous version

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Sodium mercaptoacetate CAS: 367-51-1 EC: 206-696-4	LD50 oral	200 mg/kg	Rat
	LD50 dermal	1596 mg/kg	Rat
	LC50 inhalation	>5 mg/L	
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts CAS: 61789-40-0 EC: 263-058-8	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	Non-applicable	
Alcohols, C12-13- branched and linear, ethoxylated (>= 2.5 mol EO) CAS: 160901-19-9 EC: Non-applicable	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
Sodium benzoate CAS: 532-32-1 EC: 208-534-8	LD50 oral	4070 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Alcohols, C12-13- branched and linear, ethoxylated (>= 2.5 mol EO) CAS: 160901-19-9 EC: Non-applicable	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts CAS: 61789-40-0 EC: 263-058-8	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae

12.2 Persistence and degradability:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Not available

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 30	detergents other than those mentioned in 20 01 29	Non dangerous

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

- 14.1 UN number or ID number:** Non-applicable
- 14.2 UN proper shipping name:** Non-applicable
- 14.3 Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 Packing group:** Non-applicable
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: Non-applicable
- Tunnel restriction code: Non-applicable
- Physico-Chemical properties: see section 9
- Limited quantities: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 40-20:

- 14.1 UN number or ID number:** Non-applicable
14.2 UN proper shipping name: Non-applicable
14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
14.4 Packing group: Non-applicable
14.5 Marine pollutant: No
14.6 Special precautions for user
 Special regulations: Non-applicable
 EmS Codes:
 Physico-Chemical properties: see section 9
 Limited quantities: Non-applicable
 Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

- 14.1 UN number or ID number:** Non-applicable
14.2 UN proper shipping name: Non-applicable
14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
14.4 Packing group: Non-applicable
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Sodium benzoate

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Regulation (EC) No 648/2004 on detergents:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradability criteria stipulated in Regulation (EC) n°648/2004 on detergents. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

Labelling for contents:

Component	Concentration interval
Amphoteric surfactants	% (w/w) < 5
Non-ionic surfactants	% (w/w) < 5
perfumes	

Allergenic fragrances: d-limonene (LIMONENE).

Seveso III:

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 15: REGULATORY INFORMATION (continued)

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

- Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products
- Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents
- Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII
- Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
 - Alcohols, C12-13- branched and linear, ethoxylated (≥ 2.5 mol EO) (160901-19-9)
- Removed substances
 - Alcohols, C12-13- branched and linear, ethoxylated (160901-19-9)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H311 - Toxic in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Classification procedure:

Eye Irrit. 2: Calculation method

Skin Sens. 1: Calculation method

Advice related to training:

Profipower Wheel Cleaner

Date of compilation: 25/03/2021

Revised: 08/03/2022

Version: 3 (Replaced 2)

SECTION 16: OTHER INFORMATION (continued)

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -